



DRIZORO S.A.

C/ Primavera, 50-52 - Parque Industrial Las Monjas - 28850 TORREJON DE ARDOZ - MADRID (SPAIN)

Tel. (34) 91 676 66 76 - 91 677 61 75 - Fax (34) 91 675 78 13

INTERNET: www.drizoro.com - E-mail: info@drizoro.com

EC DECLARATION OF CONFORMITY

TO WHOM IT MAY CONCERN:

We declare that our product **MAXRITE 500** meets all the provisions of EU Construction Products Directive 89/106/CE, in compliance with the Standard **UNE-EN 1504-3** as *Structural repair mortar of concrete*:

- Name of the product: **MAXRITE 500**
- Description: Structural repair mortar of concrete
- Uses: Buildings and civil engineering works

Manufactured in:

C/ Primavera, 50 Polígono Industrial Las Monjas
Torrejón de Ardoz-28850 (Madrid)

This product meets the requirements for initial type testing in accordance with the provisions of Annex ZA of the Standard **UNE-EN 1504-3**, and with the corresponding Factory Production Control, which has been certified by the notified body AENOR with number 0099/CPD/B15/0011. Information accompanying the CE marking for the product is attached at Annex A of this Declaration.

In witness whereof, this document has been signed to date of 15th February 2010.


DRIZORO, S.A.U.

Francisco Rodríguez
Director of Quality and Environment



ANNEX A:

Copy of the information accompanying the CE marking for **MAXRITE 500:**

	
DRIZORO, S.A.U. C/ Primavera 50-52 Parque Industrial Las Monjas 28850 Torrejón de Ardoz-MADRID 09	
MAXRITE 500 0099/CPD/B15/0011 EN 1504-3 PCC mortar for structural repair of concrete	
Compressive strength	Class R4
Chloride ion content	≤ 0,05 %
Adhesive bond	≥ 2,0 MPa
Carbonation resistance	Pass
Elastic modulus	> 20 GPa
Thermal compatibility Part 1, Freeze-Thaw	≥ 2,0 MPa
Thermal compatibility Part 2, Thunder shower	≥ 2,0 MPa
Thermal compatibility Part 4, Dry cycling	≥ 2,0 MPa
Capillary absorption	≤ 0,5 kg·m ⁻² ·h ^{-0,5}
Reaction to fire	A1
Dangerous substances	Comply with 5.4

