

Rasco Bitumen Emulsion SH

Solvent-free, anionic bituminous emulsion for preservation of structures or further refinement



PRODUCT FEATURES

- Solvent-free and environmentally friendly
- Anionic
- Frost-free at least 12 months shelf-life

TECHNICAL DATA

Solid content	58-59%
Density	1.0 kg/l
Viscosity*	9,500-15,000 mPa·s
Working and drying temperature**	+5°C to +30°C

* measured with Brookfield at 23 °C and 50% relative humidity

** Temperature: component, installation and ambient temperature.

DELIVERY UNITS

10-24 t tank truck, 1,000 kg Container

GENERAL NOTES

In case of sealing or maintenance work the relevant standards and guidelines must be followed.

APPLICATION

- We are happy to help you in case of questions regarding processing and refinement.
- Please contact our Research and Development department via telephone +49 5237 608-0 or via e-mail: rasco@bitumentchnik.de

SPECIAL NOTES

- Please note the Safety Data Sheet

Note: The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the Rasco product installation. For the most up-to-date TDS and warranty information, please visit our website at www.rasco-bitumen.com. Any alterations to the wording or requirements contained in or derived from this TDS shall void all related Rasco warranties.

Issue 01: This document has been issued for the first time. When this version is updated it will lose its validity.